



ZX-1 & ZX-2 Series

Fixed velocity thickness gauges

ELECTRONICS

ACOUSTIC

WEIGHT

OVERLOADING
SAFETY SYSTEMS

VALVES

TEMPERATURE

DETECT
A FIRE®

FLOW

DENSITY

INTERFACE

PRESSURE

LEVEL

TF
23



ZX-1 & ZX-2 THICKNESS GAUGES

The ZX-1 & 2 are basic fixed velocity gauges that require no special training to operate.

Calibration is done by simply scrolling to a known material velocity, or selecting a common material from a list of material types in the ZX-2. The gauges were designed and built to withstand the roughest industry conditions, are affordable, and backed by a 5 year limited warranty. If you're looking for a quality instrument to reliably meet or exceed your application expectations, look no further.

Highlights

- Easy to operate
- Pulse-echo measurement
- Dual element transducers (1-10MHz options)
- 120MHz FPGA timing
- 150 volt square wave pulser
- Low temperature custom LCD display (-22 F / -30C)
- Adjustable material velocity
- Selectable material list (ZX-2 only)
- IP65 protection rating
- 5 year limited warranty



SPECIFICATIONS

Physical	<p>Weight: 11 ounces (with batteries) Size: width (2.5 in / 63.5 mm) - Height (5.17 in / 131.3 mm) - Depth (1.24 in / 31.5 mm) Operating temperature: -22 to 167F (-30 to 75C) Case: extruded aluminum body with nickel-plated aluminum end caps (gasket sealed)</p>																																												
Keypad	Sealed membrane that is resistant to both water and petroleum products. Seven or eight tactile-feedback keys.																																												
Transducer	<p>Dual-element (transmit and receive) 1 to 10 MHz frequency range Locking quick disconnect LEMO connectors 4 foot cable Custom transducers available for special applications</p>																																												
Power Source	<p>Two 1.5V alkaline, 1.2V NiCad, or 1.5V Lithium AA cells Typically operates for 45 hours on alkaline and 23 hours on NiCad Low battery indicator on display Unit turns off automatically when battery is too low to operate reliably</p>																																												
Display	<p>Multi-function 7 segment 4.5 digit liquid crystal display with 0.500 in digit height. Two 0.125 in 14 segment fields for labels and values, and one 7 segment field for labels and values. Additional icons to indicate features and modes Backlight is selectable on/off/auto, and selectable brightness (Lo, Med, Hi) options Bar graph indicates stability of reading</p>																																												
Certification	Factory calibration traceable to NIST & MIL-STD-45662A																																												
Warranty	5 year limited																																												
Measuring	<p>Range: measures from 0.025 to 36.00 inches (0.63 to 914.4 millimeters). Range dependent on material and transducer type Units: English & Metric Resolution: 0.001 inches (0.01 millimeters) Velocity Range: 0.0120 to .7300 in/μs (305 to 18,542 m/sec) PRF: 200Hz Display update rate: 10Hz Velocity Settings: ZX-1: Adjustable on keypad. ZX-2: Adjustable on keypad and selectable from 8 factory presets and 2 programmable custom velocity options</p>																																												
Velocity Chart	<table border="1"> <thead> <tr> <th></th> <th>in.</th> <th>/</th> <th>mm</th> </tr> </thead> <tbody> <tr> <td>1. Steel 4340</td> <td>.2330</td> <td>/</td> <td>5918</td> </tr> <tr> <td>2. Stainless 303</td> <td>.2230</td> <td>/</td> <td>5664</td> </tr> <tr> <td>3. Aluminum 2024</td> <td>.2510</td> <td>/</td> <td>6375</td> </tr> <tr> <td>4. Cast Iron</td> <td>.1800</td> <td>/</td> <td>4572</td> </tr> <tr> <td>5. Plexiglass</td> <td>.1060</td> <td>/</td> <td>2692</td> </tr> <tr> <td>6. PVC</td> <td>.0940</td> <td>/</td> <td>2388</td> </tr> <tr> <td>7. Polystyrene</td> <td>.0920</td> <td>/</td> <td>2337</td> </tr> <tr> <td>8. Polyurethane</td> <td>.0700</td> <td>/</td> <td>1778</td> </tr> <tr> <td>9. Custom</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10. Custom</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		in.	/	mm	1. Steel 4340	.2330	/	5918	2. Stainless 303	.2230	/	5664	3. Aluminum 2024	.2510	/	6375	4. Cast Iron	.1800	/	4572	5. Plexiglass	.1060	/	2692	6. PVC	.0940	/	2388	7. Polystyrene	.0920	/	2337	8. Polyurethane	.0700	/	1778	9. Custom				10. Custom			
	in.	/	mm																																										
1. Steel 4340	.2330	/	5918																																										
2. Stainless 303	.2230	/	5664																																										
3. Aluminum 2024	.2510	/	6375																																										
4. Cast Iron	.1800	/	4572																																										
5. Plexiglass	.1060	/	2692																																										
6. PVC	.0940	/	2388																																										
7. Polystyrene	.0920	/	2337																																										
8. Polyurethane	.0700	/	1778																																										
9. Custom																																													
10. Custom																																													